

Arch Chemicals (Pty) Ltd

(Reg No. 1971/07322/07)



TELEPHONE + 27 11 393 9000
TELEFAX + 27 11 393 9020

P.O. BOX 114 BERGVLEI 2012 SOUTH AFRICA

SITUATED AT : NCP FACTORY SITE
HYTOR STREET
CHLOORKOP
KEMPTON PARK 1619

www.hth.co.za

To lower Total Alkalinity (TA)

1. Switch the pump off.
2. Pre-dissolve 250g of HTH® Dry Acid in 5 litres of water. Pour into one spot in the deep end of the pool.
3. Leave the pump off for 15 minutes.
4. Switch the pump on and continue with normal filtration. Check the TA level after 12 hours.
5. If necessary, repeat the process until the ideal range is reached.

Recommended Product/s:

HTH® Dry Acid

HTH® 4-in-1 Test Kit or HTH® Quick Test Strips

**All dosages are based on an average pool with a capacity of 50 000 litres.
Adjust according to your pool size, regional variations and weather conditions.**



DIRECTORS : P VODOVIC** (Chairman), A J HARDING (Managing Director) M A COOK* C A POOLMAN C G ANSLEY
(*Italian) (*USA)

HTH® & hth® are the Registered Trade Marks of Arch Inc.

